

Material Safety Data Sheet (MSDS) Report

MSDS Number: SDS201712211055

Applicant: Jiangsu Fengchi Green Power Co.,Ltd.
No.82 Xinzhong Road, Xinzhuang Street,
Yixing City, Jiangsu Province, 214200,
China

Sample Description:

Product Name : Polymer Lithium-Ion Battery Pack
Battery type : Polymer lithium-ion batteries
Nominal voltage : 24V
Nominal capacity: 6000mAh/144Wh
Battery weight : 1065g
Dimension : L: 410mm, W: 65mm, T: 26mm
Data Reviewed : Dec 21, 2017

Based on the information provided by the applicant, this Material Safety Data Sheet (MSDS) was generated in accordance with requirements of Regulation OSHA Hazard Communication Standard 29 CFR 1910.1200 (OSHA HazCom 2012), for more details please refer to the following attached pages.

This report shall not be reproduced except in full, without the written approval of Shanghai Ruifu Co.,Ltd.

Approved By:



Joey Zhang, Manager
On behalf of Shanghai Ruifu Co., Ltd.

Shanghai Ruifu Co.,Ltd.

Building 8, No.33 Jiuxin Road, Songjiang District, Shanghai, 201000, China

Tel: +86 21 67795598 E-mail: MSDS@vip.163.com Website: www.sh-ruifu.com

报告专用章

MATERIAL SAFETY DATA SHEET

Page: 1

Revision Date: 12/21/2017

MSDS Number: SDS201712211055

Version: 1.0

Polymer Lithium-Ion Battery Pack

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product name : Polymer Lithium-Ion Battery Pack
Battery type : Polymer lithium-ion batteries
Nominal voltage : 24V
Nominal capacity : 6000mAh/144Wh
Battery weight : 1065g
Physical dimension : L: 410mm, W: 65mm, T: 26mm

Recommended use of the chemical and restrictions on use

Identified use : Power supply for electronic device.

Details of the supplier of the safety data sheet

Jiangsu Fengchi Green Power Co.,Ltd
No.82 Xinzhong Road, Xinzhuang Street,
Yixing City, Jiangsu Province, 214200
China

Emergency telephone number

Tel: +86-510-87560105 or contact your local emergency center.

Product Information

Tel: +86-510-87560105
E-mail: Chenpeng422@sina.com

SECTION 2. HAZARDS IDENTIFICATION

This product containing lithium-ion battery is an article pursuant to 29 CFR 1910.1200 and, as such, is not subject to the OSHA Hazard Communication Standard requirement(HCS2012). The information contained in this Material Safety Data Sheet contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.

As a solid, manufactured article, exposure to hazardous ingredients is not expected with normal use. The potential for exposure should not exist unless the battery leaks, is exposed to high temperatures or is mechanically, electrically or physically abused/damaged. If the battery is compromised and starts to leak, based upon the battery ingredients, the contents are classified as hazardous.

The following GHS hazardous classification are derived based on the internal ingredients of battery under extreme exposure scenarios, such as breakage, leakage or being abused.



Polymer Lithium-Ion Battery Pack

GHS-Classification

Hazard classification : Flammable solids, Category 1
 Flammable solid.
 Substances and mixtures, which in contact with water, emit flammable gases, Category 2
 In contact with water releases flammable gases.
 Skin sensitisation, Category 1
 May cause an allergic skin reaction.
 Carcinogenicity, Category 2
 Suspected of causing cancer.
 Specific target organ toxicity - repeated exposure, Category 2, Inhalation
 May cause damage to organs through prolonged or repeated exposure if inhaled.

GHS-Labeling

Symbol(s) : 

Signal word : Danger

Hazard statements : H228 Flammable solid.
 H261 In contact with water releases flammable gases.
 H317 May cause an allergic skin reaction.
 H351 Suspected of causing cancer.
 H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements : **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P223 Do not allow contact with water.
 P231 + P232 Handle under inert gas. Protect from moisture.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
 P302 + P352 IF ON SKIN: Wash with plenty of water.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.

MATERIAL SAFETY DATA SHEET

Page: 3

Revision Date: 12/21/2017

MSDS Number: SDS201712211055

Version: 1.0

Polymer Lithium-Ion Battery Pack

- P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P335 + P334 Brush off loose particles from skin. Immerse in cool water/ wrap in wet bandages.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

- P402 + P404 Store in a dry place. Store in a closed container.
P405 Store locked up.

Disposal:

- P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No further available information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product form : Manufactured article

Hazardous components

| Component | CAS Number | Percent of Total Weight |
|----------------------|----------------|-------------------------|
| Organic Carbonate | Not applicable | 13-18% |
| Carbon(Graphite) | 7782-42-5 | 12-15% |
| Copper Foil | 7440-50-8 | 7-10% |
| Lithium Cobalt Oxide | 12190-79-3 | 2-3% |
| Lithium Salts | Not applicable | 1-5% |
| Nickel | 7440-02-0 | 2-5% |
| Aluminum Foil | 7429-90-5 | 5% |

The materials contained in the batter may only become a hazard if the battery or the cell is disintegrated or if the battery is physically or electrically abused. The battery should not be opened or exposed to heat because exposure of the above ingredients contained within could be harmful under some circumstances.

SECTION 4. FIRST AID MEASURES

Under normal conditions of battery use, internal ingredients/components will not present a health hazard. The following information is provided for exposures that may occur during battery production or container breakage or under extreme heat conditions such as fire.

Burning and disassembly batteries may emit acrid smoke, irritating fumes, and toxic fumes of hazardous oxides of carbons, hydrofluoric acid and other toxic by-products.

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

MATERIAL SAFETY DATA SHEET

Page: 4

Revision Date: 12/21/2017

MSDS Number: SDS201712211055

Version: 1.0

Polymer Lithium-Ion Battery Pack

- Do not leave the victim unattended.
- If inhaled : Move to fresh air.
If breathed in, move person into fresh air.
Keep patient warm and at rest.
If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
Wash contaminated clothing before re-use.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Get medical attention immediately.
Do NOT induce vomiting.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : None known
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray/Foam
Carbon dioxide (CO2)/Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : This battery product is considered safe under normal use conditions, but it will burn in case of fire.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Toxic fumes
Acrid smoke/irritating fumes
- Specific extinguishing : Product is compatible with standard fire-fighting agents.

Polymer Lithium-Ion Battery Pack

methods

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus and full protective gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Normally not required.
In the event of fire and breakage, please ensure that:
Use personal protective equipment.
Ensure adequate ventilation.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : If possible, carefully neutralize spilled electrolyte with soda ash, sodium bicarbonate, lime, etc.

Other information : Comply with all applicable national and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Use only approved chargers and procedures.
Improperly charging a cell may cause the cell or battery to flame or damage.
Do not drop battery, puncture, or attempt to open battery case.
Avoid contact with the internal components of a battery.
Do not subject product to open flame or fire and avoid situations that could cause arcing between terminals.
For personal protection see section 8.

Conditions for safe storage : Store batteries under roof in cool, dry, well-ventilated areas separated from incompatible materials and from activities that may create flames, spark, or heat.
Store sealed lead acid batteries at ambient temperature..
Observe label precautions.

Charging : Shut-off power to chargers whenever not in use and before detachment of any circuit connections.
Charging space should be ventilated.
There is a possible risk of electric shock from charging equipment and from strings of series connected batteries, whether or not being charged.

Polymer Lithium-Ion Battery Pack

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Engineering measures : Store sealed batteries at ambient temperature.
Never recharge batteries in an unventilated, enclosed space.
Do not subject product to open flame or fire.
Avoid conditions that could cause arcing between terminals.

Personal protective equipment

Respiratory protection : NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT.

Hand protection : NONE REQUIRED FOR NORMAL HANDLING OF THE PRODUCT.

Eye protection : NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT.

Skin and body protection : NONE REQUIRED FOR NORMAL HANDLING OF THE FINISHED PRODUCT.

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Manufactured article

Colour : No data available

Odour : odorless

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : No data available

Evaporation rate : No data available

Flammability : Non flammable under normal use condition.

Upper explosion limit : No data available

MATERIAL SAFETY DATA SHEET

Page: 7

Revision Date: 12/21/2017

MSDS Number: SDS201712211055

Version: 1.0

Polymer Lithium-Ion Battery Pack

| | |
|--|---------------------|
| Lower explosion limit | : No data available |
| Vapour pressure | : Not applicable |
| Relative vapour density | : No data available |
| Relative density | : No data available |
| Density | : No data available |
| Water solubility | : Insoluble |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Thermal decomposition | : No data available |
| Viscosity, dynamic | : Not applicable |
| Viscosity, kinematic | : No applicable |
| Oxidizing properties | : No data available |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|--|
| Reactivity | : No decomposition if stored and applied as directed. |
| Chemical stability | : Stable under recommended storage conditions. The sealed battery is considered stable. |
| Possibility of hazardous reactions | : Product will not undergo hazardous polymerization. |
| Incompatible materials | : None known |
| Hazardous decomposition products | None under normal operating conditions. Carbon dioxide and hydrogen fluoride gas may be generated during combustion of battery. |

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Not applicable under normal conditions of use.

Acute toxicity

Not classified based on available information.

Polymer Lithium-Ion Battery Pack

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information**Product:****Carcinogenicity:****IARC**

Cobalt in lithium cobalt oxide is considered as a class 2B carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

None Known to be human carcinogen

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

When properly used or disposed, the batteries do not present environmental hazards.

Do not let internal components enter marine environment.

Avoid release to waterways, wastewater or groundwater.

Persistence and degradability**Components:**

No data available

Bioaccumulative potential**Components:**

No data available

Mobility in soil**Components:**

No data available

Polymer Lithium-Ion Battery Pack

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Material should be recycled if possible.
The product should not be allowed to enter drains, water courses or the soil.
This material must be disposed of in a safe manner.
Send to a licensed waste management company.
Dispose of in accordance with all applicable national and local regulations.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

Lithium Ion Batteries are classified as Class 9 Dangerous Goods in the United Nations Recommendation. In case of transport, compliance with all the relevant UN regulations is required. This Polymer Lithium-Ion Battery Pack(Model: ITP2410, 24V, 10000mAh, 240Wh)has met the requirements of UN38.3 test(UN Manual of Tests and Criteria, Part III, Subsection 38.3.).

Provisions for the international transportation (pursuant to ICAO-TI/IATA-DGR, IMDG Code):

UN-No.: UN 3480
Proper Shipping Name: Lithium Ion Batteries (including lithium polymer batteries)

Polymer Lithium-Ion Battery Pack are subject to the following transport rules:

| Method | Technical Guidelines | Packing Instruction and Special Provisions |
|------------|---|---|
| Air | 2017–2018 edition of the ICAO Technical Instructions(ICAO TI) or IATA Dangerous Goods Regulations 2017 (58th Edition) | Packing Instruction 965 Section IA For Cells greater than 20 Wh; and Batteries greater than 100 Wh Limit per package: Pax A/C = Forbidden CAO = 35 kg |
| Marine/Sea | IMDG Code 2017(38-16) | Special Provision 188, 230, 310, 348, 376, 377 |

Air transportation: Shipping of lithium batteries in aircrafts are regulated by IATA and ICAO requirements in special provision A88, A99, A154, A164, A51, and A183.

Proper shipping name: Lithium ion batteries (including lithium ion polymer batteries)

UN Number: 3480

Hazard class: 9

Packing group: N/A

EQ: E0

Marine pollutant: No

Polymer Lithium-Ion Battery Pack



With effect 1 April 2016 all lithium ion cells and batteries shipped by themselves (UN 3480) are forbidden for transport as cargo on passenger aircraft. All packages prepared in accordance with Packing Instruction 965, Section IA, IB and II, must bear a Cargo Aircraft Only label, in addition to existing labels.

Sea transportation: Shipping of lithium batteries on the sea are regulated by IMDG requirements of UN3480. Exceptions found in Special Provisions 188 230 310 348 376 377.

Proper shipping name: Lithium ion batteries (including lithium ion polymer batteries)

UN Number: 3480

Hazard class: 9

Packing group: N/A

LQ: 0

EQ: E0

EmS No.: F-A,S-I

Marine pollutant: No

SECTION 15. REGULATORY INFORMATION

This product is an article pursuant to 29 CFR 1910.1200 and as such is not subjected to the OSHA Hazard Communication Standard. The information on this SDS is supplied at customer's request for information only.

SARA 302 : Not regulated.

SARA 311/312 Hazards : Not regulated.

SARA 313 Component(s) Cobalt compounds are considered hazardous and are subjected to reporting requirements of section 313 title III of the superfund amendments and reauthorization act of 1986 (SARA) and 40 CFR part 372.

California Prop 65 This product does not contain any chemical known to the State of California to cause cancer.

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 12/21/2017

Disclaimer:

This MSDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by us to be dependable and is accurate to the best of our knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

MATERIAL SAFETY DATA SHEET

Page: 11

Revision Date: 12/21/2017

MSDS Number: SDS201712211055

Version: 1.0

Polymer Lithium-Ion Battery Pack

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. We assumed no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average

*****End of report*****